

Tiemann Premium Used
Rudolf-Diesel-Straße 7
27419 Sittensen

Tel.: (0 42 82) 50 90 – 900
Fax: (0 42 82) 50 90 – 555

Samson TG 18 mit TSB2 Schleppschuhgestänge

Printout from: 21.04.2026

Internal reference number for your request:
S00001293

Year of manufacture:	2022
Design:	Manure technology + manure technology
Category:	Pumpass

EUR 199,500.⁰⁰

(plus VAT 19% EUR 237,405.⁰⁰)



Detail overview

An overview of the equipment features and the property description can be found on the following page.

Equipment

On-board computer	✓
Design	Pump
Air brake	✓
Filling quantity	18.200,00
hydr. foldable	✓
Pump capacity	10.000,00
Distributor	Trailing shoe
Tyres	Alliance 750/60R30.5
Working width	18,00
Landing gear	Tandem axle
Suspension	Hydraulic
Filling system	Suction arm
Attachment	below
Ball head K 80	✓
Forced steering	✓
Container material	Steel
Technical condition	Good

Description

- Samson TG 18 with 18 m TSB2 trailing shoe linkage
- -
- Section emptying
- Samson ejector vacuum system
- SlurryMaster 5000 control system
- 13T axle with preparation for tire pressure regulation system
- incl. electr. hydr. steering
- Front discharge pipe incl. automatic volume control
- Rigid linkage fitting for trailing shoe linkages
- incl. hydraulic wing on/off lifting/lowering and distributor
- SAP1 side docking arm with filling pump
- 8" coupling and coupling for ejector
- Alliance 750/60R 30.5 Radial Type 885 tires
- PG II Unloading pump with stone trap
- Scharmüller K80 ball head coupling with 20 cm extension
- hydr-stuetzfusz
- Central lubrication left side for manual pump 22 lubrication points
- Samson HD Night Color camera system with 9" screen and a camera at the rear of the vehicle
- Filling level switch
- Rotating beacon
- 1x LED worklight
- Ejector feed shut-off with hydraulic spade pusher and remote control left
- Filling pipe for filling the ejector reservoir when the tank level is low
- Overflow pipe for ext. filling with drain
- Mud flaps
- Bomech Preparation Plus
- Forced steering converted to K50
- -
- Samson 18 m TSB2 trailing shoe hanger
- Working width 18 m / foldable to 15 m
- Rotor Cut distributor
- Central lubrication for manual pump - 10 lubrication points
- Hydr. spade pusher for stone trap
- Samson Active Pressure Control and Adaptive Contour System with wing elevator function
- Section control with two sections controlled via hydraulic spade shutters (50/50)
- Lane barrier plates mounted in distributor outlets (6 pcs.)
- Rear adapter frame for PG and TG series
- Transport bracket for transporting the TSB 15-18-21 as individual rods
- -
- Price is valid for existing condition. Offer subject to change. Errors, changes and prior sale reserved. All

information without warranty.

- Â
- Â
- Â
- Â
- Â