

Tiemann Premium Used
Rudolf-Diesel-Straße 7
27419 Sittensen

Tel.: (0 42 82) 50 90 – 900
Fax: (0 42 82) 50 90 – 555

Fliegl Gigant ASW 3101 Taurus FOX

Printout from: 27.04.2026

Internal reference number for your request:
S00001483

Year of manufacture:	2025
Design:	Transport technology
Category:	Trailer

EUR 94,500.⁰⁰

(plus VAT 19% EUR 112,455.⁰⁰)



Detail overview

An overview of the equipment features and the property description can be found on the following page.

Equipment

Design	to the rear
Essays	Steel
Tyres	710/50R30.5
Air brake	✓
Loading volume	55,00
Steering axle	✓
Gross vehicle weight	33,00
Number of axles	3
State	Used
Technical condition	Good

Description

- fliegl-gigant-asw-3101-aurus-fox
- -----
- Tridem chassis
- zul-gesamtgewicht-33000-kg-entspricht-30000-kg-achslast-zzgl-3000-kg-stuetzlast
- Continuous hydraulically sprung towing device for bottom hitching
- Hitch height can be conveniently adjusted according to requirements, best ride comfort
- Ball head K80 (80 mm)
- Drop foot
- 2-circuit air brake with ALB
- Axle design 410 x 180 brake drum BPW
- Forced steering - 3 brake axles, front and rear steered, middle rigid,
- bereifung-71050-r-305
- Hydraulic suspension
- 40 km/h version with EC type approval and COC papers (incl. mudguards, underride guard and side marker lights)
- bruecke-9300-mm-x-2380-mm
- Rear wall and side walls 2000 mm high, with front wall height Galvanized side walls
- Hydraulic large-capacity rear wall 800 mm with grain pusher 420 mm x 250 mm (total length)
- Superstructure 10100 mm)
- Hydraulic sliding floor with all-round polyurethane strips, optimum sealing, hose routing
- Underride guard hydraulically foldable
- LED lighting 12 V with 7-pin plug
- Additional package Protect:
- -Profile filler
- -Plastic mudguard
- -Plastic rear apron
- -Outline lighting
- Climbing ladder mounted on the front side
- PTO drive shaft with cam clutch for ASW 3101/4101
- Aluminum body 300 mm side
- Lift axis
- Operation of the hydraulic functions via tractor control units
- Dosing roller for push-off trailer 2000 mm high, without rear wall, PTO shaft drive and
- Hydraulic lines (not possible in conjunction with folding underride guard)
- PTO shaft connection for connecting to the PTO drive shaft
- 2 horizontal distribution rollers with automatic feed control
- -----
- Price is valid for existing condition. Offer subject to change. Errors, changes and prior sale reserved. All information without warranty.