

Tiemann Premium Used
Rudolf-Diesel-Straße 7
27419 Sittensen

Tel.: (0 42 82) 50 90 – 900
Fax: (0 42 82) 50 90 – 555

Samson PG II 20 Genesis

Printout from: 20.02.2026

Internal reference number for your request:
MXSO/1706

Year of manufacture:	2024
Design:	Manure technology + manure technology
Category:	Vacuum Façade

Price on demand



Detail overview

An overview of the equipment features and the property description can be found on the following page.

Equipment

Design	Pump
Air brake	✓
Filling quantity	20.700,00
Tyres	Alliance VF 800/60R32
Landing gear	Tandem axle
Suspension	Hydraulic
Attachment device for application technology	3 - Punkt Hubwerk
Filling system	Suction arm
Attachment	below
Ball head K 80	✓
Forced steering	✓
Suction accelerator	✓
Container material	Steel
State	Used
Technical condition	Good

Description

- Samson PG II 20 Genesis
- -
- Amount applied: 45,500m³
- Total working time: 830h
- PG II 6" discharge pump with stone trap, ejector, hydraulic ball valve for scraper function, inspection cover, automatic application rate control, ISOBUS power supply, section emptying, filling level meter, 6" blind flange, 1 rotating beacon, 1 LED work light (1850 lumen) at the rear
- PG II 20 GENESIS tank prepared for ejector, pump tower, SAP and permanently installed filling pump
- SAMSON green and epoxy coating from the inside for PG II 20 GENESIS
- SlurryMaster 8000 incl. joystick, PVG 5, distributor, dosing boom on off, wing off on, incl. LS control and electronic wheel control
- SlurryMaster 8000 ISOBUS function (TC-GEO/TC-SC)Â
- Manual support foot
- Hydraulic drawbar suspension with variable drawbar eye positionÂ
- Tires: ALLIANCE 800/60R32 VF 389 AGRIFLEX+ (axle load 10,000 kg)Â
- Air pressure brake incl. axlesÂ
- Cardan shaft 1 3/8, wide angle 6 pcs.
- ScharmÂ¼ller K 80 ball head coupling with 20 cm extension
- SAP II Mk2 incl. filling pump, 8" head and coupling for ejector
- Hydraulic actuation for emptying the stone catcher trough
- Drainage pipeÂ
- Filling funnel with removable valve plate
- Central lubrication with pump - 46 lubrication pointsÂ
- Central lubrication hoist (only with central lubrication) - 8 lubrication points
- Central lubrication SAP II (only with central lubrication)Â
- Central lubrication connection for devices at the rear
- Welded preparation for FAP on the drum including internal ejector connection
- Blind flange for FAP preparation
- Category 3 lifting gear incl. electric operation at the rearÂ
- active hoist incl. height position sensorÂ
- 5 double-acting connections (spade slide valve/ADS/inclined position/50-50 or TD12)
- Free unpressurized oil return for other attachments
- V4000 compressor for tire pressure controlÂ
- 1-circuit tire pressure control systemÂ
- Electronic fill level control
- Filling pump at the side

- On/off switch for side filling pump
- HELLA LED headlights 4 units and 1 extra unit at the rear - 18850 lumens in total
- SAMSON HD NIGHT COLOR camera system incl. 9" screen and 1 camera on the back (can manage up to 4 cameras)
- Ejector feed shut-off with hydraulic spade valve and remote control on the left of the drum
- Water tank 15 l for manual cleaning
- Mud flaps
- Filler pipe for SAP II with 8" Bauer coupling 90°
- Filling hose for SAP II Mk2
- Preparation BOMECH Plus PG II 18-20-28-31-35 G
- Air outlet on the back of the enamel trolley
- -
- Price is valid for existing condition. Offer subject to change. Errors, changes and prior sale reserved. All information without warranty.
-
-