Tiemann Landtechnik GmbH & Co. KG

Tiemann Premium Used
Rudolf-Diesel-Straße 7
27419 Sittensen

Tel.: (0 42 82) 50 90 – 900
Fax:

Samson PG II 20 Genesis

Printout from: 04.11.2026

Internal reference number for your request:
MXSO/1706

Year of manufacture:	2024
Design:	Manure technology + manure technology
Category:	Vacuum Façade

EUR 189,000.^{00}

(plus VAT 19% EUR 224,910.^{00})





Detail overview

An overview of the equipment features and the property description can be found on the following page.

Equipment

Design	Pump
Air brake	✔
Filling quantity	20.700,00
Tyres	Alliance VF 800/60R32
Landing gear	Tandem axle
Suspension	Hydraulic
Attachment device for application technology	3 - Punkt Hubwerk
Filling system	Suction arm
Attachment	below
Ball head K 80	✔
Forced steering	✔
Suction accelerator	✔
Container material	Steel
State	Used
Technical condition	Good

Description

• Samson PG II 20 Genesis
• -
• ausgebrachte-menge-53500m
• PG II 6" discharge pump with stone trap, ejector, hydraulic ball valve for scraper function, inspection cover, automatic application rate control, ISOBUS power supply, section emptying, filling level meter, 6" blind flange, 1 rotating beacon, 1 LED work light (1850 lumen) at the rear
• PG II 20 GENESIS tank prepared for ejector, pump tower, SAP and permanently installed filling pump
• SAMSON green and epoxy coating from the inside for PG II 20 GENESIS
• SlurryMaster 8000 incl. joystick, PVG 5, distributor, dosing boom on off, wing off on, incl. LS control and electronic wheel control
• SlurryMaster 8000 ISOBUS function (TC-GEO/TC-SC)Â
• Manual support foot
• Hydraulic drawbar suspension with variable drawbar eye positionÂ
• Tires: ALLIANCE 800/60R32 VF 389 AGRIFLEX+ (axle load 10,000 kg)Â
• Air pressure brake incl. axlesÂ
• Cardan shaft 1 3/8, wide angle 6 pcs.
• Scharmüller K 80 ball head coupling with 20 cm extension
• SAP II Mk2 incl. filling pump, 8" head and coupling for ejector
• Hydraulic actuation for emptying the stone catcher trough
• Drainage pipeÂ
• Filling funnel with removable valve plate
• Central lubrication with pump - 46 lubrication pointsÂ
• Central lubrication hoist (only with central lubrication) - 8 lubrication points
• Central lubrication SAP II (only with central lubrication)Â
• Central lubrication connection for devices at the rear
• Welded preparation for FAP on the drum including internal ejector connection
• Blind flange for FAP preparation
• Category 3 lifting gear incl. electric operation at the rearÂ
• active hoist incl. height position sensorÂ
• 5 double-acting connections (spade slide valve/ADS/inclined position/50-50 or TD12)
• Free unpressurized oil return for other attachments
• V4000 compressor for tire pressure controlÂ
• 1-circuit tire pressure control systemÂ
• Electronic fill level control
• Filling pump at the side
• On/off switch for side filling pump

• HELLA LED headlights 4 units and 1 extra unit at the rear - 18850 lumens in total
• SAMSON HD NIGHT COLOR camera system incl. 9" screen and 1 camera on the back (can manage up to 4 cameras)
• Ejector feed shut-off with hydraulic spade valve and remote control on the left of the drum
• Water tank 15 l for manual cleaningÂ
• Mud flaps
• Filler pipe for SAP II with 8" Bauer coupling 90°
• Filling hose for SAP II Mk2
• Preparation BOMECH Plus PG II 18-20-28-31-35 GÂ
• Air outlet on the back of the enamel trolley
• -
• Price is valid for existing condition. Offer subject to change. Errors, changes and prior sale reserved. All information without warranty.